Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SUWL2120C-5

208V Three Phase Whip in 5 ft length with L21-20R output for 3 Phase Distribution Cabinet Applications

Highlights

- 208V three phase whip distribution cabinet accessory
- 5 ft. length with 3 ft. removed outer jacket
- 5 conductor 12AWG stranded wire
- L21-20R outlet (208V 3PH 20A)

Description

208V three phase whip with L21-20R outlet distributes power from 3 phase distribution cabinet to critical equipment racks. 5 ft. insulated and 3 ft. of removed outer jacket cabling supports hardwire connection to SUBB320 circuit breaker in SUDC208V series 3 phase distribution racks. L21-20R outlet is compatible with 208V loads and Power Distribution Units (PDUs) supporting a L21-20P plug-in connection.

Specifications

OVERVIEW	
Model Type	Whips
OUTPUT	
PDU recommendation notes	Compatible with all PDU brands fitted with a L21-20P (208V 3PH 20A) input plug, including Tripp Lite PDU3MV6L2120, PDU3MV6L2120B, PDU3MV6L2120LV, PDU3VN10L2120, PDU3VN10L2120LV, PDU3VN3L2120, PDU3VN3L2120LV, PDU3VSR10L2120 and PDU3VSR3L2120
Outlet Type	L21-20R (1)
INPUT	
Input connection type	Hardwire (5 wire - L1, L2, L3, N, G)
Cable Length (ft.)	5
Cable Length (m)	1.52
PHYSICAL	
Shipping weight (lbs)	4.8
Shipping weight (kg)	1.7
Unit weight (lbs)	3.8
Unit weight (kg)	2.2
Color	Black
WARRANTY	

Product Warranty Period (Worldwide)	1-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=5398.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.